



SUPERSIX / CAAD10

| SPECIFICATIONS | 48 | 50 | 52 | 54 | 56 | 58 | 60 | 63 |
|--|------|------|------|------|------|------|-------|-------|
| A Horizontal Top Tube Length (cm) | 51.5 | 52.5 | 53.5 | 54.5 | 56.0 | 57.5 | 59.0 | 60.0 |
| B Measured Size (cm)* | 46 | 48 | 50 | 52 | 54 | 56 | 58 | 61 |
| C Seat Tube Angle (degrees) | 74.5 | 74.5 | 74 | 73.5 | 73.5 | 73 | 72.5 | 72 |
| D Head Tube Angle (degrees) | 72 | 72.5 | 73 | 73 | 73 | 73.5 | 73.5 | 73.5 |
| E Chain Stay Length (cm) | 40.5 | ★ | ★ | ★ | ★ | ★ | 40.8 | 40.8 |
| F Fork Rake (cm) | 4.5 | ★ | ★ | ★ | ★ | ★ | ★ | ★ |
| G Bottom Bracket Height (cm) | 26.5 | 26.5 | 26.5 | 26.8 | 26.8 | 27.0 | 27.0 | 27.0 |
| H Wheelbase (cm) | 95.9 | 96.6 | 96.8 | 97.5 | 99.2 | 99.6 | 100.1 | 101.3 |
| I Trail (cm) | 6.2 | 5.9 | 5.6 | 5.6 | 5.6 | 5.3 | 5.3 | 5.3 |
| J Standover at Top Tube Midpoint (cm) | 74 | 75.3 | 76.5 | 78.5 | 80.1 | 82.2 | 83.8 | 86.6 |
| K Bottom Bracket Drop (cm) | 7.2 | 7.2 | 7.2 | 6.9 | 6.9 | 6.7 | 6.7 | 6.7 |
| L Front Center Distance (cm) | 56.5 | 57.2 | 57.4 | 58.0 | 59.7 | 60.1 | 61.0 | 61.4 |
| M Head Tube Length (cm) | 11 | 11.5 | 12.0 | 14.0 | 15.5 | 17.5 | 19.0 | 22.0 |
| N Stack (cm)** | 51.7 | 52.3 | 52.9 | 54.6 | 56.0 | 57.9 | 59.3 | 62.2 |
| O Reach (cm) | 36.8 | 37.8 | 38.2 | 38.3 | 39.4 | 39.9 | 40.4 | 39.9 |

* The measured size is from the center of the bottom bracket to the top of the top tube, measured along the seat tube axis.

All sizes have a slightly sloping top tube.

** Stack is measured vertically from the center of the BB to the top of the head tube, reach is measured horizontally from the center of the BB to the top of the head tube.